

| Voltage Range<br>DC Load Side<br>VDC | Power Range<br>DC Load Side<br>kW | Current Range<br>DC Load Side<br>A | Model Number             | Height<br>U | Line Voltage<br>3L<br>VAC | Line Frequency<br>Hz     | Physical Dimensions<br>W x H x D<br>mm / in |
|--------------------------------------|-----------------------------------|------------------------------------|--------------------------|-------------|---------------------------|--------------------------|---|
| <b>400 VAC</b>                       |                                   |                                    |                          |             |                           |                          |   |
| <b>0 - 52 V</b>                      | 0 - 10 kW                         | 0 - 250 A                          | <b>TC.P.10.52.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 16 kW                         | 0 - 400 A                          | <b>TC.P.16.52.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 20 kW                         | 0 - 500 A                          | <b>TC.P.20.52.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
|                                      | 0 - 32 kW                         | 0 - 700 A                          | <b>TC.P.32.52.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
| <b>0 - 65 V</b>                      | 0 - 10 kW                         | 0 - 193 A                          | <b>TC.P.10.65.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 16 kW                         | 0 - 308 A                          | <b>TC.P.16.65.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 20 kW                         | 0 - 385 A                          | <b>TC.P.20.65.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
|                                      | 0 - 32 kW                         | 0 - 600 A                          | <b>TC.P.32.65.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
| <b>0 - 100 V</b>                     | 0 - 10 kW                         | 0 - 125 A                          | <b>TC.P.10.100.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 16 kW                         | 0 - 200 A                          | <b>TC.P.16.100.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 20 kW                         | 0 - 250 A                          | <b>TC.P.20.100.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
|                                      | 0 - 32 kW                         | 0 - 400 A                          | <b>TC.P.32.100.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
| <b>0 - 130 V</b>                     | 0 - 10 kW                         | 0 - 96 A                           | <b>TC.P.10.130.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 16 kW                         | 0 - 153 A                          | <b>TC.P.16.130.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 20 kW                         | 0 - 192 A                          | <b>TC.P.20.130.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
|                                      | 0 - 32 kW                         | 0 - 308 A                          | <b>TC.P.32.130.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |

| Voltage Range<br>DC Load Side<br>VDC | Power Range<br>DC Load Side<br>kW | Current Range<br>DC Load Side<br>A | Model Number             | Height<br>U | Line Voltage<br>3L<br>VAC | Line Frequency<br>Hz     | Physical Dimensions<br>W x H x D<br>mm / in |
|--------------------------------------|-----------------------------------|------------------------------------|--------------------------|-------------|---------------------------|--------------------------|---|
| <b>400 VAC</b>                       |                                   |                                    |                          |             |                           |                          |   |
| <b>0 - 200 V</b>                     | 0 - 10 kW                         | 0 - 63 A                           | <b>TC.P.10.200.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 16 kW                         | 0 - 100 A                          | <b>TC.P.16.200.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 20 kW                         | 0 - 125 A                          | <b>TC.P.20.200.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
|                                      | 0 - 32 kW                         | 0 - 200 A                          | <b>TC.P.32.200.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
| <b>0 - 320 V</b>                     | 0 - 20 kW                         | 0 - 80 A                           | <b>TC.P.20.320.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
|                                      | 0 - 32 kW                         | 0 - 125 A                          | <b>TC.P.32.320.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
| <b>0 - 400 V</b>                     | 0 - 10 kW                         | 0 - 31 A                           | <b>TC.P.10.400.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 16 kW                         | 0 - 50 A                           | <b>TC.P.16.400.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 20 kW                         | 0 - 63 A                           | <b>TC.P.20.400.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
|                                      | 0 - 32 kW                         | 0 - 100 A                          | <b>TC.P.32.400.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
| <b>0 - 500 V</b>                     | 0 - 10 kW                         | 0 - 25 A                           | <b>TC.P.10.500.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 16 kW                         | 0 - 40 A                           | <b>TC.P.16.500.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 20 kW                         | 0 - 50 A                           | <b>TC.P.20.500.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
|                                      | 0 - 32 kW                         | 0 - 80 A                           | <b>TC.P.32.500.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |

| Voltage Range<br>DC Load Side<br>VDC | Power Range<br>DC Load Side<br>kW | Current Range<br>DC Load Side<br>A | Model Number              | Height<br>U | Line Voltage<br>3L<br>VAC | Line Frequency<br>Hz     | Physical Dimensions<br>W x H x D<br>mm / in |
|--------------------------------------|-----------------------------------|------------------------------------|---------------------------|-------------|---------------------------|--------------------------|---|
| <b>400 VAC</b>                       |                                   |                                    |                           |             |                           |                          |   |
| <b>0 - 600 V</b>                     | 0 - 10 kW                         | 0 - 20 A                           | <b>TC.P.10.600.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 16 kW                         | 0 - 32 A                           | <b>TC.P.16.600.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 20 kW                         | 0 - 40 A                           | <b>TC.P.20.600.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
|                                      | 0 - 32 kW                         | 0 - 66 A                           | <b>TC.P.32.600.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
| <b>0 - 800 V</b>                     | 0 - 10 kW                         | 0 - 16 A                           | <b>TC.P.10.800.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 16 kW                         | 0 - 25 A                           | <b>TC.P.16.800.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 20 kW                         | 0 - 32 A                           | <b>TC.P.20.800.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
|                                      | 0 - 32 kW                         | 0 - 50 A                           | <b>TC.P.32.800.400.S</b>  | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
| <b>0 - 1000 V</b>                    | 0 - 10 kW                         | 0 - 13 A                           | <b>TC.P.10.1000.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 16 kW                         | 0 - 20 A                           | <b>TC.P.16.1000.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 6 U x 495 mm / 19" | 44 kg / 97 lbs                              |
|                                      | 0 - 20 kW                         | 0 - 25 A                           | <b>TC.P.20.1000.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
|                                      | 0 - 32 kW                         | 0 - 40 A                           | <b>TC.P.32.1000.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
| <b>0 - 1200 V</b>                    | 0 - 20 kW                         | 0 - 20 A                           | <b>TC.P.20.1200.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |
|                                      | 0 - 32 kW                         | 0 - 33 A                           | <b>TC.P.32.1200.400.S</b> | 360 - 440 V | 48 - 62 Hz                | 19" x 9 U x 570 mm / 22" | 64 kg / 141 lbs                             |