

Voltage Range DC Load Side VDC	Power Range DC Load Side kW	Current Range DC Load Side A	Model Number	Height U	Line Voltage 3L VAC	Line Frequency Hz	Physical Dimensions W x H x D mm / in
480 VAC							
0 - 52 V	0 - 20 kW	0 - 500 A	TC.P.20.52.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
	0 - 32 kW	0 - 700 A	TC.P.32.52.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
0 - 65 V	0 - 20 kW	0 - 385 A	TC.P.20.65.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
	0 - 32 kW	0 - 600 A	TC.P.32.65.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
0 - 100 V	0 - 20 kW	0 - 250 A	TC.P.20.100.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
	0 - 32 kW	0 - 400 A	TC.P.32.100.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
0 - 130 V	0 - 20 kW	0 - 192 A	TC.P.20.130.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
	0 - 32 kW	0 - 308 A	TC.P.32.130.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
0 - 200 V	0 - 20 kW	0 - 125 A	TC.P.20.200.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
	0 - 32 kW	0 - 200 A	TC.P.32.200.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
0 - 400 V	0 - 20 kW	0 - 63 A	TC.P.20.400.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
	0 - 32 kW	0 - 100 A	TC.P.32.400.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
0 - 500 V	0 - 20 kW	0 - 50 A	TC.P.20.500.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
	0 - 32 kW	0 - 80 A	TC.P.32.500.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs

Voltage Range DC Load Side VDC	Power Range DC Load Side kW	Current Range DC Load Side A	Model Number	Height U	Line Voltage 3L VAC	Line Frequency Hz	Physical Dimensions W x H x D mm / in
480 VAC							
0 - 600 V	0 - 20 kW	0 - 40 A	TC.P.20.600.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
	0 - 32 kW	0 - 66 A	TC.P.32.600.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
0 - 800 V	0 - 20 kW	0 - 32 A	TC.P.20.800.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
	0 - 32 kW	0 - 50 A	TC.P.32.800.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
0 - 1000 V	0 - 20 kW	0 - 25 A	TC.P.20.1000.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
	0 - 32 kW	0 - 40 A	TC.P.32.1000.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
0 - 1200 V	0 - 20 kW	0 - 20 A	TC.P.20.1200.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs
	0 - 32 kW	0 - 33 A	TC.P.32.1200.480.S	432 - 528 VAC	48 - 62 Hz	19" x 9 U x 590 mm / 23"	64 kg / 141 lbs