

DECKBLATT ZUM ORIGINAL-DOKUMENT DES HERSTELLERS

16KW | DATENBLATT GERÄTE

HERSTELLER Regatron AG

PRODUKTSERIE TopCon Quadro-Serie [16kW_500V]

Ihr direkter Ansprechpartner für Regatron-Produkte!

Die Ing. Erhard Fischer GmbH ist Ihr zuverlässiger Partner für die Produkte von Regatron AG. Wir bieten Ihnen nicht nur hochwertigen technischen Support, sondern auch kompetente Beratung und maßgeschneiderte Lösungen für Ihre individuellen Anforderungen.

Ob Standardprodukt, kundenspezifische Geräte oder Schaltschrankbau. Wir freuen uns, Sie bei Ihrer Lösungsfindung mit eingehender Kundenberatung kompetent unterstützen zu können.

Kontaktieren Sie uns für technische Beratung oder ein individuelles Angebot!

Wir freuen uns auf das Gespräch mit Ihnen.



IHR ANSPRECHPARTNER

Martin Sochor



+43 2236 42694-40



powersupply@ing-fischer.at



Ing. Erhard Fischer GmbH



Weissenbach 101 | AT-2371 Hinterbrühl



www.ing-fischer.at



ING. ERHARD FISCHER GMBH
**Immer die passende Lösung für Industrie-
Stromversorgungen, Heizfolien & Messtechnik**

TC.P.16.500.400.S

Programmable DC Power Supply (TopCon Quadro)

- 16 kW
- 500 V
- 40 A

Features

- Unidirectional power supply
- Proven dynamics
- Cost effective
- TopControl operating SW + API



Key Values

| | | |
|---|---|-------------------------|
| Power | | 16 kW |
| Voltage DC | limited by P_{max} | 500 V |
| Current | limited by P_{max} and ambient temperature | 40 A |
| Autoranging factor | $U_{max} \times I_{max} / P_{max}$ | 1.25 |
| <i>Figure 1</i> | | |
| Master-slave / multi-device configuration | | parallel, series, mixed |
| Max. number of devices in system | may be extended by TC.MAC | 16 |
| Max. number in parallel | may be extended by TC.MAC | 16 |
| Max. number in series | with midpoint earthing limited by output isolation to PE | 4 |
| Case | | 19" / 6U |

AC Lineside Rating

| | | |
|------------------------------------|------------------------|--------------------------------|
| Mains connection type | delta | 3L + PE (no neutral necessary) |
| Rated voltage | | 3x400 V $\pm 10\%$ |
| Rated current | @nominal 3x 360 VAC | 30 A _{rms} |
| | @nominal 3x 380 VAC | 29 A _{rms} |
| | @nominal 3x 400 VAC | 27 A _{rms} |
| | @nominal 3x 415 VAC | 26 A _{rms} |
| | @nominal 3x 440 VAC | 25 A _{rms} |
| Rated frequency | | 50/60 Hz |
| Power factor | @ P_{max} | 0.92 |
| THDi | @90% P_{max} | 32% |
| Input stage | | 6 pulse bridge rectifier |
| Efficiency | $P_{max} @ U_{max}$ | 94% |
| Input insulation test voltage | line to case/logic | 1670 VDC (1 s) |
| Protective earth conductor current | According to IEC 60990 | <10 mA |
| Touch current unweighted | | 20 mA |
| Touch current weighted | | 2 mA |
| Input filter discharge | L-PE / L-L | 6.9s/8.8s |
| <i>to <60 V</i> | | |
| | with option XCD | <1 s |

DC Operation

| | | |
|--|--------------|----------------------|
| Operation modes | | Source |
| Voltage regulation | CV | 0...100% U_{max} |
| Current regulation | CC | 0...100% I_{max} |
| Power regulation | CP | 5...100% P_{max} |
| Internal resistance simulation | programmable | 0...12500 m Ω |
| Load regulation | voltage | 0.1% FS |
| <i>0...100% load</i> | | |
| <i>At 25° ambient temperature, constant line input</i> | | |
| | current | 0.1% FS |

DC Operation (continued)

| | | | |
|--|--|---|-------------|
| Line regulation -10%...+10% line voltage At 25° ambient temperature, constant load | voltage | 0.1% FS | |
| | current | 0.1% FS | |
| HMI meter resolution | programming/reading | 0.1 V 0.1 A | |
| | X-capacitor | 87 µF | |
| Output capacitance | Y-capacitor @DC | 13.6 nF | |
| | Ripple, voltage | output voltage ripple 300 Hz V_{rms} ohmic load, CV mode Typical value at nominal ohmic load, line asymmetry < 1 V_{rms} | ≤0.4% FS |
| output voltage ripple 300 Hz V_{pp} ohmic load, CV mode Typical value at nominal ohmic load, line asymmetry < 1 V_{rms} | | ≤1.1% FS | |
| Noise | | noise 40 kHz...1 MHz V_{rms} ohmic load, CV mode tpical value at nominal ohmic load, line asymmetry < 1 V_{rms} | < 0.1 V |
| | | noise 40 kHz...1 MHz V_{pp} ohmic load, CV mode tpical value at nominal ohmic load, line asymmetry < 1 V_{rms} | < 1.5 V |
| Stability/drift 8h, after 1h warm up time in output on state, at constant line input, load and temp. conditions | voltage | ≤0.05% FS | |
| | voltage sense | ≤0.05% FS | |
| | current | ≤0.05% FS | |
| Temperature coefficient At constant line and load conditions | voltage | ≤0.02% FS/°C | |
| | current | ≤0.03% FS/°C | |
| Rise/fall time (10...90% of step) Voltage set-value step, const. ohmic load | voltage step (10...90% U_{max} / 10...90% P_{max}) can be affected in multi-unit operation | <2 ms | |
| | Rise/fall time (10...90% of step) Current set-value step, const. ohmic load | current step (10...90% I_{max}) 10...90% of step can be affected in multi-unit operation | <2 ms |
| Transient response time Load step, ohmic load | | CV, recovery within 5% set voltage 10...90% P_{max} can be affected in multi-unit operation | <2 ms |
| | Transient response time Load step, ohmic load | CC, recovery within 5% of set current 10...90% P_{max} can be affected in multi-unit operation | <2 ms |
| Protection | | OVP (over voltage protection) programmable | 0...110% FS |
| | OCP (over current protection) programmable | 0...110% FS | |
| | OPP (over power protection) programmable | 0...110% FS | |
| | OTP (over temperature protection) | ✓ | |
| Output discharge to <60V | | <420ms | |
| Sense voltage compensation | | Programmable Uout + Udrop limited by Uout _{max} | |
| Sense input impedance | | 452 kΩ | |
| Ballast resistor DC power port | @output off | 2.5 kΩ | |
| Resistance | DC+/DC- output to PE | open | |
| | X109 jumper inserted | | |
| Absolute maximum ratings | Voltage | 550 | |
| | Current | 44 | |
| | DC+ output to PE | +1500 V / -1000V | |
| | DC- output to PE | +1000 V / -1000V | |

DC Operation (continued)

| | | |
|--------------------------------|----------------------|----------------|
| Input insulation test voltage | line to case/logic | 1670 VDC (1 s) |
| Output insulation test voltage | output to case/logic | 2540 VDC (1 s) |

Various

| | | |
|------------------------------------|--|---|
| Case dimensions <i>Figure 3</i> | H × W × D without terminals | 265 × 483 × 450 mm 10 1/2" × 19" × 17 3/4" |
| Weight | | 44 kg / 97 lbs |
| AC terminals | screw terminals | 10 mm ² |
| DC terminals | | Output bars for M8 bolts |
| Enclosure | rating current bars on rear side excluded | IP20 |
| Communication interface | | RS232 (38400 baud) |
| | isolation to electronics and case | 125 V |
| | resolution, programming and readbck U, I | 0.025% FS |
| | resolution, programming and readbck P, Ri | 0.1% FS |
| Option cards | # of free slots | 1 |

Analog Inputs

| | | |
|------------------------------|--|------------------|
| Number of inputs | setvalues for voltage, current, power, and internal resistance | 4 |
| Resolution | | 12 Bit |
| Sampling rate | | 20 kHz |
| Input voltage range | 0...100% FS | 0...10 V |
| Isolation | to electronics and case | 125 V |
| Input impedance | | 20 kΩ (typ.) |
| Absolut max. input voltage | | 30 VDC |
| Input filter | bandwidth programmable | OFF, 0.1...400Hz |
| Delay analog in to power out | can be affected in multi-unit operation | 200 μs (typ.) |

Analog Outputs

| | | |
|-------------------------------|---|------------------|
| Number of outputs | voltage, current readback | 2 |
| Resolution | | 12 Bit |
| Update rate | | 10 kHz |
| output filter | bandwidth programmable | OFF, 0.1...400Hz |
| Output voltage range | 0...100% FS | 0...10 V |
| Isolation | to electronics and case | 125 V |
| Output impedance | | 535 Ω (typ.) |
| Max. output current | short-circuit proof | 28 mA |
| Delay power out to analog out | can be affected in multi-unit operation | 200 μs (typ.) |

Digital I/O

| | | |
|---|---------------------|---|
| Number of digital inputs | | 6 (4 inputs programmable, + voltage on, +interlock) |
| Output voltage supplied for digital I/O | | 24 VDC (-15% / +20%) |
| Input impedance | | 4.7 kΩ |
| Max. voltage digital inputs | | 30 VDC |
| Sampling rate digital inputs | | 1 kHz |
| Max total output current all channels | | 200 mA |
| Max output current per channel | short-circuit proof | 200 mA |
| Update rate digital outputs | | 10 kHz |

Relay Outputs

| | | |
|-------------------------|---|-----------------------------|
| Number of relay outputs | Error: SPST(NO) Run: SPST(NO) Warn: 1× SPDT | 3 |
| Load type | | ohmic, inductive, lamp load |
| Max. switching voltage | | 30 VDC |
| Max. switching current | | 1 A |
| Switching time | | 20 ms (typ.) |

Ambient

| | | |
|--|--|--|
| Operating altitude | above sea level above 1000 m / 3280 ft, slight temp. derating possible | ≤2000 m / ≤6562 ft |
| Operating temperature | with airfilter | 5...40 °C -10 °C |
| Current derating | max. continuous output current @ temperature: higher current if CDF <100% no derating if equipped with optional liquid cooling | 40°C: 32 A |
| Storage temperature | | -25...+70 °C |
| Installation | IEC 60721-3-3 | indoor, air-conditioned in protected 19" switch cabinet |
| Orientation | storage, installation, operation | upright |
| Relative humidity | non-condensing | 0...95% |
| Vibration | IEC 60068-2-6 | Test Fc |
| Cooling | | direct forced air, front to back optional liquid cooling (85%), AC100 (Al-Ti-alloy) |
| Acoustic noise level <i>1 m dist. front (typ.)</i> | 90% P _{max} , 90% I _{max} @25 °C ambient | 63 dB(A) |

Standards

| | | |
|---|--|-------------------|
| Protection class | EN 62477-1 | 1 |
| Degree of pollution | EN 60664-1 | 2 |
| Overvoltage category | mains input, EN 60664-1 / EN 62477-1 other interfaces | III II |
| Area of application | | industrial |
| Approval | | CE marking, UKCA |
| EN 62477-1:2012 <i>+ A11:2014 + A1:2017 + A12:2021</i> | Low Voltage Directive 2014/35/EU | ✓ |
| BS EN 62477-1:2012 <i>+ A11:2014 + A1:2017 + A12:2021</i> | Electrical Equipment (Safety) Regulations 2016 | ✓ |
| EN ISO 13849-1:2015 | w/o ISR with ISR 2-channel with ISR 2-channel and external safety relay | - PL c PL e |
| EN 61000-6-4:2007 A1:2011 / EN61000-6-4:2019 | Directive 2014/30/EU EMC emission (industrial) | ✓ |
| BS EN 61000-6-4:2007 A1:2011 / <i>BS EN61000-6-4:2019</i> | Electromagnetic Compatibility Regulations 2016 EMC emission (industrial) | ✓ |
| EN 61000-6-2:2005 / EN 61000-6-2:2019 | Directive 2014/30/EU EMC immunity (industrial) | ✓ |
| BS EN 61000-6-2:2005 / BS EN 61000-6-2:2019 | Electromagnetic Compatibility Regulations 2016 EMC immunity (industrial) | ✓ |
| EN IEC 63000:2018 | RoHS Directive | ✓ |
| BS EN IEC 63000:2018 | The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 | ✓ |

Operating area




Figure 1: TC.P.16.500.400.S, voltage / current operating area.
Max.current up to 400 V
Max.Voltage up to 32 A

Dimensions




Figure 3: Front, side, and rear view. 19-inch module with 4 units in height.

This product is developed, produced and tested according to ISO 9001 by REGATRON.

For detailed technical information, contact REGATRON or your local sales partner.

| | |
|--|---|
| Regatron AG Feldmuehlestrasse 50 9400 Rorschach SWITZERLAND | Regatron Inc. 100 Overlook Center, 2 nd Floor Princeton, NJ 08540 USA |
| sales@regatron.com www.regatron.com | inquiries@us.regatron.com www.us.regatron.com |

All product specifications and information contained herein are subject to change without notice.

Filename: DS_TC.P.16.500.400.S_EN_2024-09-19

Class: Public

T038